

32" LED HD COLOR MONITOR GTS-32LEDMON



This professional grade widescreen LED 32" Full HD color monitor offers HDMI, VGA, Looping BNC, S-Video, and Looping Audio. This monitor combines extremely high contrast and low power consumption to be the perfect deploy-anywhere option.

- 32" Diagonal Viewing Size
- 1920 X 1080 HD Resolution
- HDMI, VGA, BNC I/O, S-Video, & Audio I/O
- One-Touch Button 4:3 Scale Toggle
- Includes HDMI, Audio, VGA Cable, Remote
- 24/7/365 UL Rated Operating Capability
- 2 Built-in Stereo Speakers
- 200mm x 100mm VESA Mounting Pattern
- 30 month warranty

PART #: **GTS-32LEDMON**
UPC: **811914027140**
LENGTH: **29.3"**
WIDTH: **2.31"**
HEIGHT: **17.45"**
WEIGHT: **19.4 lbs**
UL LISTING: **E470702**



SPEC SHEET

Model	GTS-27LEDMON	GTS-32LEDMON
Screen diagonal dimension (in)	27	32
Viewable area W x H (inches)	23.54*13.24mm	27.50*15.47mm
Led Type	LED	
Pixel Pitch (mm)	0.3114	0.36
Screen Maximum Resolution	1920x1080	
Supported Panel Display Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1920x1080;	
Supported Input Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1920x1080;	
Refresh Rate	60, 70, 75 Hz depending on resolution	
Color Space/Gamut	Deep Color	
Color Depth	16.7M	
Brightness	250 CD/m2	300 CD/m2
Auto Adjust	Yes	
Monitor Aspect Ratio	16:09	
Display Aspect Ratio	OSD selectable 16:9 or 4:3	
Horizontal TV Lines	1080	
Contrast Ratio	1000 : 1	3000 : 1
Response Time (ms)	8	6.5
View Angle H/V (degrees)	178/178	
Digital Video Inputs	HDMI up to 1920x1080	
Analog Video In/Out	VGA up to 1920x1080	
Audio inputs (stereo)	1x 3.5mm mini-jack	
Speakers	Two - built in 2"	
Stand-by	<0.5watts	
Power Consumption	≤35W	<55W
Monitor Body Dimensions (W x L x D)	24.52*14.46*1.92	29.30*17.45*2.31
Max Dimensions Monitor + Stand (in)	24.52*17.78*6.95	29.30*20.26*13.75
Panel Surface	Front bezel, high glossy; back cover, matte finish; base high glossy	Front bezel, matte finish; back cover, matte finish; base matte finish
Case & Stand Material	Plastic	
VESA Mounting Pattern	75x75;	200x100;
Base/Stand included	Yes	
Base Tilt Angle	+15° --10°	
Weight Cabinet only (lb.)	12.3	19.4
Weight Cabinet + Base Stand (lb)	14.8	23.8
Power Supply (internal)	AC 100-240V~50/60Hz 2A	
Operating Temperature	0°C ~ 50°C	
Storage Temperature	-20°C ~ 50°C	
Operating Humidity	10 - 90%	
Accessories	VGA cable/Audio cable/User manual/Power cable/HDMI cable	
Certifications	UL/CE/FCC/ROHS/HDMI	
Warranty	30 months	

FOR MORE INFORMATION, CONTACT YOUR GTS SALES PERSON.

Phone: (800) 941-8878 e-mail: sales@galardy.com

www.galardy.com