

 **TRIVIEW®**

# Universal IP Camera Test Monitor

- 4.3 OLED Display with Touchscreen
- Works with Multiple IP Camera Brands & Analog Cameras
- Supports PoE
- Internal Battery with Charger Included
- Snap Shot & Video Functions
- Test For Wire Runs
- RJ45 Connection for Ethernet & BNC for Analog
- Supports Firmware Updates\*
- 3 year warranty

**TOM-0431IP** is an IP and Analog installation and service tool that works with a variety of the most popular IP camera brands. The TOM-0431IP is highly portable and includes a 4.3" touch screen display in wide-screen format, RJ45 connector for ethernet connection and BNC input and output for analog use. The unit incorporates PoE function as well as a 8 gig MicroSD card & USB port for storage of "Snapshot and Video." The TOM-0431IP also tests for wire pin alignment to ensure you have a proper cable installation. A carrying case along with a velcro wrist strap is included for hands-free operation. The battery powered TOM-0431IP includes a cable for charging the unit's internal battery.



**INCLUDES:**  
VELCRO WRIST STRAP  
& CARRYING BAG

# TOM-0431 IP

## 4.3" OLED Touch Screen Test Monitor



Rechargeable Li-ion battery  
 Tests for Wire Pin Alignment  
 IP and Analog  
 PoE, SnapShot & Video Function  
 Micro SD Card Slot & USB

Screen Size	4.3" Diagonal
Technology	OLED
Aspect Ratio	16:9
View Angle H/V	-80°, +80°/-80°, +80°
Contrast Ratio	10,000:1
Brightness	250 cd/m <sup>2</sup>
Resolution	480 x 272
Response Time	2ms
Display Color	16.7M
Input Voltage	12VDC / 3.0A
Consumption	<6.5W
Charger	Input: 100~240VAC, 1.3A, 50-60Hz, Output: 12VDC/3.0A
Battery	7.2VDC/2600MAH 2-Cell Li-ion Battery (Embedded Inside The Device)
Memory	8GB MicroSD Card Included (MicroSD Slot Supports Up To 32GB) 1GB Internal Memory
Input	Composite Video, Connector: 1 BNC Level: 1.0Vp-p / 75Ω 2 RJ45; LAN IN and PoE/Power Bank IN
Output	1 BNC Connector for CVBS Loop-Through and Test Pattern Output 1 RJ45; CAT-5 Cable Tester
Video Support	NTSC and PAL
Charging Time	3.5 Hours Average
Operating Time	Continuous Display Time: 3-Hours Average (2-Hours PoE ON) Standby Time: 6+ Hours
Operating Temperature	32° F-104° F
Dimensions	5.6" x 1.06" x 3.74"
Weight	Net: 12oz / Gross: 3lbs 4oz

