

# 4.3" OLED **HD Analog Test Monitor**

## Supports AHD and TVI **High Definition Analog Cameras**

**OLED Panel for Sunlight Readable Includes 12DV Output to Power Cameras** Auto Detect PAL and NTSC Signals Rechargeable Li-Ion Internal Battery 4-Hour Operating and Charging Time

### **TOM-043A**

Screen Size 4.3" OLED Viewing Angle 160° / 160° Contrast Ratio 1000:1 Resolution 480 x 272 Luminance 250 cd/m<sup>2</sup> 2ms

Response Type

#### **Input Connectors:**

**BNC In - Standard CVBS** 1 (PAL / NTSC)

BNC In - Analog HD 1 (AHD 2.0 / TVI) 1000TVL 720/1080P

Audio (Phone Jack) 1 (Stereo Audio Input)

#### **Output Connectors:**

**BNC Out - Standard CVBS** 1 (PAL / NTSC Passive Loop-Thru Output) BNC Out - Analog HD 1 (AHD 2.0 / TVI Passive Loop-Thru Output)

#### **Other Connectors**

DC12V Out 1 (DC12V Out / 0.5A, For Cameras)

DC12V Power In 1 (<6.5 watts)

**Internal Battery** 7.2DC Li-lon 2600mAH Battery

**Power Consumption** < 6.5 watts

**Power Supply** Power Adapter AC100-240V / Monitor: DV12V/3A

Dimension 5.6: x 1.06" x 3.74"

Weight Product 0.5 lbs / Packaging 2 lbs

Regulatory CE, FCC, RoHS

**Includes** Standard Velcro Wrist Band, User Manual, DC12V Power Adapter, Power Cord, and DC Output Cable