TM SERIES 24"-50"

Economic Wide Security and Digital Signage Displays



| | | | | |
|---------------------|---|---|---|---|
| Model | TME24 (LED) | TME32 (LED) | TME42 (LED) | TME50 (LED) |
| Screen Size | 23.6" Wide | 31.5" Wide | 42" Wide | 50" Wide |
| Aspect Ratio | 16:9 & Opt 4:3 | 16:9 & Opt 4:3 | 16:9 & Opt 4:3 | 16:9 & Opt 4:3 |
| Max Resolution | 1920 x 1080 | 1920 x 1080 | 1920 x 1080 | 1920 x 1080 |
| Brightness | 200cd/m² | 300cd/m ² | 330cd/m ² | 300cd/m ² |
| Contrast Ratio | 800:1 | 1200:1 | 1400:1 | 4000:1 |
| Response Time | 5ms | 8ms | 8ms | 8ms |
| Viewing Angle | 150/140 | 178/178 | 178/178 | 160/120 |
| Display Color | 16.7M | 16.7M | 16.7M | 16.7M |
| Power Consumption | <40W | <60W | <98W | <130W |
| Power | AC 120-240V | AC 120-240V | AC 120-240V | AC 120-240V |
| Input/Output | VGA DVI via adapter through HDMI (DVI to HDMI adapter is not included) HDMI 1.4 BNC In x 1 (via adapter, 1 included) BNC Out x 1 (via adapter, 1 included) (when monitor is on and Input selection is at AV In) Audio In Built-In Speakers USB Port x 2 (MPEG-4, JPEG, MP3, .TXT) | VGA DVI via adapter through HDMI (DVI to HDMI adapter is not included) HDMI 1.4 x 2 Component video – YpPbPr BNC In x 1 (via adapter, 1 included) BNC Out x 1 (via adapter, 1 included) (when monitor is on and Input selection is at AV In) AV Input x 2 / AV Output x 1 Audio In Built-In Speakers USB Port x 2 (MPEG-4, JPEG, MP3, .TXT) | VGA DVI via adapter through HDMI (DVI to HDMI adapter is not included) HDMI 1.4 x 2 Component video – YpPbPr BNC In x 1 (via adapter, 1 included) BNC Out x 1 (via adapter, 1 included) (when monitor is on and Input selection is at AV In) AV Input x 2 / AV Output x 1 Audio In Built-In Speakers USB Port x 2 (MPEG-4, JPEG, MP3, .TXT) | VGA DVI via adapter through HDMI (DVI to HDMI adapter is not included) HDMI 1.4 x 2 Component video – YpPbPr BNC In x 1 (via adapter, 1 included) BNC Out x 1 (via adapter, 1 included) (when monitor is on and input selection is at AV in) AV Input x 2 / AV Output x 1 Audio In Built-In Speakers USB Port x 2 (MPEG-4, JPEG, MP3, .TXT) |
| Speaker Output | 3W + 3W | 5W + 5W | 8W + 8W | 8W + 8W |
| VESA Mounting Holes | 100mm x 100mm | 200mm x 100mm | 300mm x 200mm | 400mm x 300mm |
| Dimensions (WxDxH) | With No Base 22.18"x2"x13.43" Height With Base 14.75" Base Dimensions 6.25"x10.62" | With No Base 29"x2.67"x18.18" Height With Base 20.25" Base Dimensions 8.68"x13.68" | With No Base 38.18"x3"x22.62" Height With Base 25" Base Dimensions 9"x17.25 | With No Base 44.69"x3"x26.02" Height With Base 29" Base Dimensions 11.5"x20.75" |
| Gross Weight | 10.7 lb | 20 lb | 34.1 lb | 44.09 lb |

Specifications subject to change without notice

