

TLM '06 SERIES

Standard Security LCD MONITORS

"Bridging the Gap between Quality and Affordability"



BNC With Loop Thru
S-Video
Audio
VGA
High Brightness
Rack, Pole, and Wall Mount
Easy Access Connections

 **TRIVIEW™**

TRIVIEW is a trademark of Tatung Company of America, Inc.

TLM '06 SERIES

Standard Security LCD MONITORS



SPECIFICATIONS

	TLM-1506 Series	TLM-1706 Series	TLM-1906 Series
Screen Size	15" diagonal	17" diagonal	19" diagonal
Viewable Size	304.1mm (H) x 228.1mm (V)	337.9mm (H) x 270.3mm (V)	376.3.1mm (H) x 301.0mm (V)
Dot Pitch	0.297mm (H) x 0.297mm (V)	0.264mm (H) x 0.264mm (V)	0.294mm (H) x 0.294mm (V)
View Angle H/V	140(H)/125(V)	160(H)/160(V)	160(H)/160(V)
Contrast Ratio	500:1	1000:1	1000:1
Brightness	450 cd/m ²	300 cd/m ²	300 cd/m ²
Resolution	1024 x 768	1280 x 1024	1280 x 1024
Response Time	8ms	5ms	5ms
Display Color	16.2M	16.7M	16.7M
Power Supply			
Input-Voltage	100~240Vac	100~240Vac	100~240Vac
Consumption	32W max.	32W max.	40W max.
Video			
Input	Composite video, connector: 1 BNC S-Video, Connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω	Composite video, connector: 1 BNC S-Video, Connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω	Composite video, connector: 1 BNC S-Video, Connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω
Output	1 BNC connector for CVBS loop-through output	1 BNC connector for CVBS loop-through output	1 BNC connector for CVBS loop-through output
System	Scanning Frequency	Scanning Frequency	Scanning Frequency
Compatibility	NTSC: 15750Hz +/- 500Hz/60Hz PAL: 15625Hz +/- 500Hz/50Hz	NTSC: 15750Hz +/- 500Hz/60Hz PAL: 15625Hz +/- 500Hz/50Hz	NTSC: 15750Hz +/- 500Hz/60Hz PAL: 15625Hz +/- 500Hz/50Hz
Analog VGA			
Input	Analog RGB: 0.707Vp-p / 75Ω, Connector: 15 pin D-Sub	Analog RGB: 0.707Vp-p / 75 , Connector: 15 pin D-Sub	Analog RGB: 0.707Vp-p / 75 , Connector: 15 pin D-Sub
Plug & Play	DDC2B	DDC2B	DDC2B
Power			
Management	VESA DPMS	VESA DPMS	VESA DPMS
Support Timing	VESA VGA / SVGA / XGA	VESA VGA / SVGA / XGA	VESA VGA / SVGA / XGA
Audio			
Input/Output	Connector: 2 x RCA connector	Connector: 2 x RCA connector	Connector: 2 x RCA connector
Speaker	Level: 1.0Vp-p / 1 KHz 2W x 2 embedded	Level: 1.0Vp-p / 1 KHz 2W x 2 embedded	Level: 1.0Vp-p / 1 KHz 2W x 2 embedded
Dimension	356x387x200mm (with base) 356x300x67mm (without base)	387x402x200mm (with base) 387x338x67mm (without base)	458x416x215mm (with base) 458x373x77mm (without base)
Weight	9.0lbs / 4.1 Kg (with base)	11.0lbs / 5.0 Kg (with base)	14.5lbs / 6.4 Kg (with base)
Additional Benefit	Rack Mountable (19" standard rack, EIA-310-D) VESA mount 100x100mm ² RoHs compliant	Rack Mountable (19" standard rack, EIA-310-D) VESA mount 100x100mm ² RoHs compliant	Rack Mountable (19" standard rack, EIA-310-D) VESA mount 100x100mm ² RoHs compliant
Mount Options	TRK-1506 Rack Mount TPM-1506 Pole Mount TWM-1506 Wall Mount TWM-DA1520 Dual Arm Mount	TRK-1706 Rack Mount TPM-1706 Pole Mount TWM-1706 Wall Mount TWM-DA1520 Dual Arm Mount	TRK-1906 Rack Mount TPM-1906 Pole Mount TWM-1906 Wall Mount TWM-DA1520 Dual Arm Mount