

# X SERIES LCD MONITORS



## FEATURES

600 TVL
2 Composite BNC Inputs
S-Video and DVI-I Input
Anti-Reflection Glass
3D Comb Filter, 3D Video De-Interlaced
Digital Noise Reduction (DNR)
Color Transient Improvement (CTI)
Picture Freeze
Rack Mountable
VESA Mount 100x100 <sup>2</sup>
Fast Response Time
Up to 1000:1 Contrast Ratio (on selected models)
Up to 300 cd/m <sup>2</sup> (on selected models)
Available In 15", 17", and 19"

Specifications Subject To Change Without Notice



Triview introduces its newest line of LCD Monitors, the X Series. The X Series is available in 15", 17", and 19", featuring 600 TVL horizontal resolution with a 4:3 aspect ratio. The X Series is an excellent solution for displaying high quality images from high resolution 520-540TVL cameras.

# X SERIES

## LCD MONITORS



Model	THR15X	THR17X	THR19X
Screen Size	15" (4:3)	17" (5:4)	19" (5:4)
Dot Pitch	0.297mm x 0.297mm	0.264mm x 0.264mm	0.294mm x 0.294mm
Viewing Angle H/V	140° / 130°	160° / 160°	170° / 160°
Contrast Ratio	500:1	1000:1	1000:1
Brightness	250 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>
Resolution	1024 x 768	1280 x 1024	1280 x 1024
Response Time	8ms	5ms	5ms
Display Color	16.2M	16.7M	16.7M
Video Input	Composite video, connector: 2 BNC, S-video, connector: 1 mini din 4 pin, Level: 1.0Vp-p / 75Ω		
Video Output	2 BNC connector for CVBS loop-through output		
DVI-I Input (with converting cable)	DDWG compliant Single Link TMDS Digital Visual Interface and Analog RGB		
Support Timing	VESA VGA / SVGA / XGA	VESA VGA / SVGA / XGA / SXGA	
Audio Input	Connector: 2 X stereo jack, Level: 1.0Vp-p / 1 KHz		
Speaker	1w x 2 embedded		
Power Consumption	36W max.	40W max.	42W max.
Power Supply	Power Adapter: 100-240V <sub>AC</sub> / Monitor: 12V <sub>DC</sub> / 4.16A		
Dimensions (WxDxH)	13.3 x 13.7 x 7.4 inches	14.6 x 13.7 x 7.4 inches	16.5 x 15.9 x 7.4 inches
Gross Weight	6.63 lbs	8.97 lbs	9.6 lbs

Specifications subject to change without notice

