

CAMERA SERIES



ZX-580SR200 – 5.8GHz FM-Live 580-Line Starlight IR-200’ 4-9mm Varifocal All Weather Wireless Camera

All NEW and easy to install, this dynamic all-weather wireless video camera transmits 5.8GHz, FM Live Real-Time video from **300 feet up to 4 miles**, depending on optional receiver. This Rugged 580 line, high resolution camera features a **4-9mm varifocal** zoom lens and is perfect for protecting property and assets with exceptional night-vision ranging up to 200 Feet.



ADVANTAGES


- Easy to Install and Operate “Plug & Play”
- 5.8GHz FM Live Real-Time Video up to 4 Miles
- Night Vision Range up to **200 Feet**
- 580 Line High-Resolution Day/Night Color Camera
- Convenient Adjustable External Focus and Zoom
- On Screen Display Menu for Convenient Video Setup
- Integrated Samsung W-IV Digital Signal Processor
- Universal 3 Axis Mounting Bracket Included
- Rugged All Weather IP-66 Rated Cast Aluminum Design
- Deters Vandalism, Theft and other Criminal Behavior

APPLICATIONS INCLUDE

ZX-580SR200




CONSTRUCTION SITES



FREEWAY



HARBOR



BRIDGES



PARKING LOTS



AIRPORTS



INDUSTRIAL



MARINAS

SPECIFICATIONS

OPERATING FREQUENCY	5.725GHz – 5.875GHz; 8 User Selectable Channels
RADIATED POWER	50mV/m @ 3m
RANGE (LINE-OF-SIGHT)	300 Feet up to 4 Miles Depending on Optional Receiver & Antenna (Sold Separately)
ANTENNA TYPE	3dB Omni-Directional Rubber Duck
VIDEO FORMAT	NTSC
CAMERA TYPE	Integrated Samsung W-IV Digital Signal Processor / 1/3" Day/Night Sony Super HAD CCD
RESOLUTION	580 Lines (Color) 700 Lines (B&W)
LENS TYPE	4.0mm - 9.0mm Varifocal Lens
INFRARED	Up to 200 Feet Night Vision Range with 36 High Intensity IR LEDs
MINIMUM ILLUMINATION	0.003 LUX @ F1.2
ON SCREEN DISPLAY MENU	Adjust Exposure, White Balance, Color, Sharpness, Motion Detection ON / OFF, Privacy Masking, Monitor Mode & Dead Pixel Compensation
CONSTRUCTION	Rugged All-Weather IP-66 Rated Cast Aluminum Design
TEMPERATURE RANGE	-30°F to +170°F
OPERATING VOLTAGE	12VDC Model # PS-121A
CURRENT CONSUMPTION	300mA @ 12VDC IR OFF / 500mA @ 12VDC IR ON
DIMENSIONS	10.30" x 4.0" x 6.10"
MOUNTING BRACKETS	Included – Universal 3 Axis Mounting Bracket
WEIGHT	840g or 1.8 lbs
FCC / IC APPROVED	Yes

KIT INCLUDES

- ALL WEATHER WIRELESS SONY IR CAMERA
- ONE OMNI-DIRECTIONAL RUBBER DUCK ANTENNA
- ONE 12VDC POWER SUPPLY
- ONE UNIVERSAL 3 AXIS MOUNTING BRACKET
- ONE MOUNTING BRACKET TEMPLATE
- OWNERS MANUAL
- ONE YEAR LIMITED WARRANTY
- RECEIVER NOT INCLUDED



www.VideoTransmitters.com

US Office: 1711 Cudaback Avenue, Niagara Falls, NY USA 14303

Canadian Office: 1016C Sutton Drive, Unit 6, Burlington, ON Canada L7L 6B8

Toll Free: 1.888.379.2666 Tel: 905.336.9665 Fax: 905.336.9662

© Copyright 2012 Printed in Canada

Take us
with you!



ZX-580SR200
Online Specs